## PATENT COOPERATION TREATY

# **PCT**

REC'D 2 3 MAR 2006

INTERNATIONAL PRELIMINARY REPORT ON PATEMERS ILPOT ROVIE

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference	FOR FURTHER ACTION See Form PCT/IPEA/416		CT/IPEA/416					
303813WO/PRS/GJS	TOKT OKTABATION							
International application No.		ernational filing date (day/month/year) Priority date (day/month/year)						
PCT/IB2004/004250	16-12-2004							
International Patent Classification (IPC) o	r national classification and IP	C						
See Supplemental Box								
Applicant	Auglicont							
Nokia Corporation et al								
1. This report is the international pre-	<ol> <li>This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.</li> </ol>							
2. This REPORT consists of a total of _5 sheets, including this cover sheet.								
3. This report is also accompanied b	by ANNEXES, comprising:							
a. (sent to the applicant	t and to the International Bure	au) a total of 5	sheets, as follows:					
sheets of the	description claims and/or dray	wings which have	been amended and are the basis of this report					
and/or sheets	s containing rectifications authone ve Instructions).	orized by this Aut	hority (see Rule 70.16 and Section 607 of the					
sheets which	supersede earlier sheets, but v	which this Authori	ty considers contain an amendment that goes					
beyond the d	lisclosure in the international a	pplication as filed	, as indicated in item 4 of Box No. I and the					
Supplementa								
b (sent to the Internati	<i>ional Bureau only)</i> a total of (ir	ndicate type and n	umber of electronic carrier(s))					
G	, containing a	elating to Sequen	and/or tables related thereto, in electronic ce Listing (see Section 802 of the					
Administrative Instr		clating to bequein	ac Listing (coo better					
4. This report contains indications	relating to the following items:	:						
<u> </u>	of the report							
Box No. II Priorit								
Box No. III Non-e	stablishment of opinion with re	egard to novelty,	nventive step and industrial applicability					
	of unity of invention							
1 1	-	5(2) with regard to	novelty, inventive step or industrial					
applic	ability; citations and explanation	ons supporting su	ch statement					
	in documents cited							
Box No. VII Certai	in defects in the international a	pplication						
Box No. VIII Certai	Box No. VIII Certain observations on the international application							
Date of submission of the demand		ate of completion	of this report					
19-10-2005		6-03-2006	5					
Name and mailing address of the IPEA/SE		authorized officer	,					
Patent- och registreringsverket Box 5055								
S-102 42 STOCKHOLM		Göran Magnusson/MN						
Facsimile No. +46 8 667 72 88	T	Telephone No. +46 8 782 25 00						

Form PCT/IPEA/409 (cover sheet) (April 2005)

# INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

III ERWINON A COMPANY OF THE PROPERTY OF THE P	PCT/IB2004/004250
Supplemental Box	
In case the space in any of the preceding boxes is not sufficient.  Continuation of: Cover sheet	
INTERNATIONAL PATENT CLASSIFICATION (IPC):	
<b>G01S 1/00</b> (2006.01)	
1	

# INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IB2004/004250

Box	No. I	Basis of the report	
1.	With re	egard to the language, this report is based on:	
	$\boxtimes$	the international application in the language in which it was filed	
		a translation of the international application into which is the language of a translation furnished for the purposes of:	,
		international search (Rules 12.3(a) and 23.1(b))	
		publication of the international application (Rule 12.4(a))	
		international preliminary examination (Rules 55.2(a) and/or 55.3(a))	·
2.	furnish	regard to the <b>elements</b> of the international application, this report is based on seed to the receiving Office in response to an invitation under Article 14 are referred e not annexed to this report):  the international application as originally filed/furnished	(replacement sheets which have been d to in this report as "originally filed"
	$\bowtie$	the description:	
		pages <u>1-24</u>	as originally filed/furnished
		pages* received by this Authority on	
	$\boxtimes$	the claims:	
		pages	as originally filed/furnished
		pages	r with any statement) under Article 19
		pages* 25-29 received by this Authority on pages* received by this Authority on	2003 10 13
	$\boxtimes$	the drawings: pages 1-7	as originally filed/furnished
		pages 1-7 pages* received by this Authority on	
•		pages* received by this Authority on	
	П	a sequence listing and/or any related table(s) - see Supplemental Box Relating to	Sequence Listing.
		1) 11 d 11-16-1 - 6	
3.	Ш	The amendments have resulted in the cancellation of:	
		the description, pages	
		the claims, Nos.	
		the drawings, sheets/figs	
		the sequence listing (specify):	
		any table(s) related to the sequence listing (specify):	
4.		This report has been established as if (some of) the amendments annexed to the made, since they have been considered to go beyond the disclosure as filed, as if 70.2(c)).	is report and listed below had not been ndicated in the Supplemental Box (Rule
		the description, pages	
1		the claims, Nos.	
		the drawings, sheets/figs	
		the sequence listing (specify):	
		any table(s) related to the sequence listing (specify):	
*	If ite	m 4 applies, some or all of those sheets may be marked "superseded."	

International application No.

PCT/IB2004/004250

Box No. V	Reasoned statement uncitations and explanation	der Article 3: ons supportin	5(2) with regard to novelty, inventive step or industrial applicability g such statement	·•
1. Statemen	t			
Nove	elty (N)	Claims Claims	1-23	YES NO
Inve	ntive step (IS)	Claims Claims	1-23	YES NO
Indu	strial applicability (IA)	Claims	1-23	YES

### 2. Citations and explanations (Rule 70.7)

The invention concerns a GPS device and solves the problem of maintaining synchronisation to GPS system time.

Documents cited in the International Search Report:

Claims

D1: EP 1130415 A D2: US 6122506 A D3: EP 1092987 A

Document D1 describes a GPS device comprising a first circuit (GPS receiver 9,10) arranged to receive a first signal and output first timing information and a second circuit (radio wave clock block 4-6) arranged to receive a second signal and output second timing information. A third circuit 3 produces third timing information dependent on the first and second initially information is timing The third signals. synchronised to the first timing information (see paragraph [0038], lines 30-39) and maintained substantially synchronised to the first signal using the second timing information (see paragraphs [0047] and [0049]).

Document D2 discloses the combination of a GPS receiver with a cellular telephone wherein a GSM reference generator 102 and a cellular communications signal including a frequency correction signal is used for obtaining a frequency reference for the GPS receiver (see column 3, lines 48-62; column 7, lines 39-57 and figure 8).

Document D3 discloses a system similar to D1.

However, none of the documents disclose the producing of a

.../...

### INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/IB2004/004250

#### Supplemental Box

In case the space in any of the preceding boxes is not sufficient. Continuation of: Box  $\,V\,$ 

location estimate dependent on the first and third timing information, the third timing information being maintained synchronised to the first signal using a cellular reference clock.

The cited prior art does not give any indication that would lead a person skilled in the art to the claimed device and method. Therefore, the claimed invention is not obvious to a person skilled in the art.

Accordingly, the invention defined in claims 1-23 is novel and is considered to involve an inventive step. The invention is industrially applicable.

PCT / IB 2004 / 0 0 4 2 5 0 1 9 -10- 2005

Claims

5

10

15

20

25

30

1. A GPS device comprising:

a first circuit arranged to receive at least one first signal and arranged to output first timing information dependent on said first signal;

a second circuit arranged to receive at least one second signal and arranged to output second timing information dependent on said second signal; and

a third circuit arranged to determine timing information of said device, said third circuit arranged to receive at least one of said first and second timing information, and further arranged to produce a third timing information dependent on at least one of received first and second signals,

wherein said third circuit is further arranged to produce a location estimate dependent on said first and third timing information;

wherein said third timing information is initially synchronised to said first timing information and maintained substantially synchronised to said at least one first signal using said second timing information; and

wherein said third circuit further comprises a cellular reference clock and wherein said third timing information is further maintained substantially synchronised to said at least one first signal using said cellular reference clock.

- 2. A device claimed in claim 1 wherein said first signal comprises a Global Positioning Satellite system signal.
- 3. A device as claimed in claims 1 or 2, wherein said second signal comprises a cellular network control or communications signal.

- 4. A device as claimed in claims 1 to 3, wherein said first timing information comprises at least one of:
  - a demodulated Global Positioning Satellite system time;
- 5 at least one Global Positioning Satellite system pseudo-range;
  - a demodulated Global Positioning Satellite system timing data word.
- 10 5. A device as claimed in claims 1 to 4, wherein said second timing information comprises at least one of:

cellular network base station symbol timing; cellular network base station frame timing.

- 15 6. A device as claimed in claims 1 to 5, wherein said first circuit comprises a Global Positioning Satellite receiver.
- 7. A device as claimed in claims 1 to 6, wherein said second circuit comprises a cellular network receiver.
  - 8. A device as claimed in any previous claim, wherein said third circuit comprises:
    - a GPS demodulator;
- 25 a timing estimator;
  - a location estimator; and
  - a clock register.
- 9. A device as claimed in claim 6, wherein said first 30 circuit further comprises:
  - a GPS demodulator; and
  - a timing estimator.

- 10. A device as claimed in claim 9, wherein said third circuit comprises:
  - a location estimator and a clock register.
- 5 11. A device as claimed in any previous claim, wherein said second and third circuit is implemented in a single circuit.
- 12. A device as claimed in any previous claim, wherein said device further comprises a threshold circuit arranged to further substantially synchronise said third timing information to said at least one first signal dependent on a threshold event.
- 13. A device as claimed in claim 12, wherein said threshold circuit is arranged to further substantially synchronise said third timing information using said first timing information.
- 14. A device as claimed in claims 12 or 13, wherein said threshold event comprises at least one of:
  - a time period;

25

- a movement of said device out of a building;
- a movement of said device following a period of relative static nature;
  - a determined number of base station handovers;
    - a received first signal strength threshold;
    - a number of received first signals.
- 15. An integrated circuit comprising a GPS device as 30 claimed in any previous claim.
  - 16. A device as claimed in claim 8 wherein said clock register comprises random access memory.

17. A method for determining the position of a device using GPS, the device comprising a cellular reference clock, the method comprising the steps of:

receiving at least one first signal;

5

15

20

producing first timing information dependent on said at least one first signal;

receiving at least one second signal;

producing second timing information dependent on said 10 at least one second signal;

producing third timing information dependent on said at least one of said first and second timing information;

initially synchronising said third timing information to said first signal, maintaining synchronisation to said first signal using said second timing information, and further maintaining synchronisation to said first signal using said cellular reference clock, and

determining a location of said device dependent on said first timing information and said third timing information, wherein said determining step comprises the step of calculating a difference between said third timing information and said first timing information to determine location estimates.

- 25 18. A method as claimed in claim 17, wherein said step of receiving at least one first signal comprises; receiving at least four GPS signals.
- 19. A method as claimed in claim 18, wherein said step of groducing at least one first timing information further comprises;

processing said at least four received GPS signals to determine at least four GPS timing signals;

processing said at least four GPS timing signals to produce a true GPS timing signal.

20. A method as claimed in claim 17, wherein said step of receiving at least one second signal comprises;

receiving at least one communications or control signal from a wireless cellular communications system base station.

- 21. A method as claimed in claims 18 to 20, wherein said step of producing said third timing information comprises a further step of triggering a threshold circuit arranged to further substantially synchronise said third timing information to said at least one first signal dependent on a threshold event.
  - 22. A method as claimed in claim 21, wherein said further step of triggering said threshold circuit is arranged to further substantially synchronise said third timing information using said first timing information.
    - 23. A method as claimed in claims 21 and 22, wherein said step of triggering said threshold circuit further comprised the detection of a threshold event comprising at least one of:
- 25 a time period;

5

15

20

30

- a movement of said device out of a building;
- a movement of said device following a period of relative static nature;
  - a determined number of base station handovers;
- a received first signal strength threshold;
  - a number of received first signals.